



NL4MDXX-H-2

This connector is fully compliant to the device standard IEC 62368-1, due to its component certification according to IEC 61984.

4 pole chassis connector, black D-size flange, mirrored self tapping screw holes (A-screw), horizontal PCB mount.

The speakON panel mount connectors are the standard chassis connectors for loudspeaker / amplifier interconnections. They feature a unique metal locking system, making contact only once fully locked. The speakON receptacles are robust, versatile and easy to terminate.

Features & Benefits

- | | |
|--|--|
| <ul style="list-style-type: none">• IEC 61984 certified > IEC 62368-1 compliant | <ul style="list-style-type: none">• Glass reinforced V-0 materials make it extremely robust and dependable |
| <ul style="list-style-type: none">• Precise keyway for secure mating | <ul style="list-style-type: none">• Accurate twist lock latching system |
| <ul style="list-style-type: none">• Metal insert in locking area | <ul style="list-style-type: none">• Airtight design - optimized for speaker applications |

Technical Information

Produkte	
Title	NL4MDXX-H-2
Gender	male

Elektrisch	
Contact resistance	$\leq 2 \text{ m}\Omega$
Dielectric strength	2.8 kVac
Insulation resistance	$>0.1 \text{ G}\Omega$ (after dampheat)
Rated current per contact	25 A rms continuous (audio rating significantly higher, depending on signal)
Rated voltage	250 V ac
Attention	speakON is NOT to be used as an AC mains or power supply connector!

Mechanische Daten	
Lifetime	> 5000 mating cycles
Wiring	Horizontal PCB mount
Locking device	Quick Lock
Mounting direction	Rear mounting
Chassis shape	D
Layout	Mirrored hole position, self tapping screw holes (A-Screw)

Material	
Contact plating	Ag
Locking element	Stainless Steel
Shell	Polyamide (PA 6.6)
Contacts	Copper Alloy

Umwelt	
Flammability	UL 94 V-0
Temperature range	-30 °C to +80 °C