



NLT4FPXX-BAG

4-polige Einbaubuchse, schwarzes Metallgehäuse, Lötanschlüsse, Durchgangsmontagelöcher

Aufgrund er Komponentenzertifizierung gemäss IEC 61984 erfüllt dieser Steckverbinder die Gerätenorm IEC 62368-1.

Die speakON STXX Lautsprecher Steckverbinder wurden für anspruchsvollste Anwendungen insbesondere im Aussen- und Touringbereich entwickelt. Durch das stabile Metalldruckguss-Gehäuse sind die Steckverbinder extrem robust.

Features & Benefits

- ✓ IEC 61984 certified, IEC 62368-1 compliant
- ✓ Extremely robust metal housing and glass reinforced V-0 material insert designed for harsh and demanding environment
- ✓ Uses precise “Quick Lock” system
- ✓ Weatherproof built-in gasket meets IP 54 protection class in mated condition

Technical Information

Produkte	
Title	NLT4FPXX-BAG
Gender	Female

Elektrisch

Contact resistance	< 2 mΩ
Dielectric strength	2.8 kVac
Insulation resistance	>0.1 GΩ (after dampheat)
Rated current per contact	30 A rms continuous
Rated voltage	250 V ac
Attention	speakON is NOT to be used as an AC mains or power supply connector!

Mechanische Daten

Lifetime	> 5000 mating cycles
Wiresize	6 mm²
Wiresize	10 AWG
Termination	Solder contacts
Locking device	Quick Lock
Mounting direction	Rear / front mounting
Chassis shape	square G-size flange
Layout	four thru holes

Material

Contact plating	Ag
Contacts	Copper Alloy
Shell	Zinc diecast, black chrome plated
Insert	Polyamide (PA 66)
Locking element	Zinc diecast, Ni plated

Umwelt	
Temperature range	-30 °C to +80 °C
Flammability	UL 94 V-0
Protection class	IP 54 (mated condition)
Solderability	Complies with IEC68-2-20