



NLT4FXX-BAG

4 pole female cable connector, black metal housing, chuck type strain relief

This connector is fully compliant to the device standard IEC 62368-1, due to its component certification according to IEC 61984.

The speakON STXX Series was especially designed for heavy duty amplifier-loudspeaker applications like professional touring. The extremely rugged and durable STXX Series features an all metal housing.

Features & Benefits

IEC 61984 certified, IEC 62368-1 compliant

Extremely robust metal housing and glass reinforced V-0 material insert designed for harsh and demanding environment

Uses precise "Quick Lock" system

Extra large solder contacts for up to 6 mm² (AWG 10) wires

Weatherproof built-in gasket meets IP 54 protection class in mated condition

Technical Information

| Produkte | |
|----------|-------------|
| Title | NLT4FXX-BAG |
| Gender | female |

| Elektrisch | |
|---------------------------|---|
| Contact resistance | < 2 mΩ |
| Dielectric strength | 2.8 kVac |
| Insulation resistance | >0.1 GΩ (after dampheat) |
| Rated current per contact | 30 A rms continuous |
| Rated voltage | 250 V ac |
| Attention | speakON is NOT to be used as an AC mains or power supply connector! |

| Mechanische Daten | |
|-------------------|----------------------|
| Cable O.D. | 9 - 16 mm |
| Lifetime | > 5000 mating cycles |
| Wiresize | 6 mm ² |
| Wiresize | 10 AWG |
| Termination | Solder contacts |
| Locking device | Quick Lock (latch) |

| Material | |
|-----------------|-----------------------------------|
| Contact plating | Ag |
| Contacts | Copper Alloy |
| Shell | Zinc diecast, black chrome plated |
| Insert | Polyamide (PA 66) |
| Locking element | Zinc diecast, Ni plated |
| Strain relief | Polyacetal (POM) |
| Shell coating | Black KTL |

| Umwelt | |
|-------------------|--------------------------|
| Temperature range | -30 °C to +80 °C |
| Flammability | UL 94 V-0 |
| Protection class | IP 54 (mated condition) |
| Solderability | Complies with IEC68-2-20 |